



Thinking of you
Electrolux

Electrolux Professional Line 5000

Electrolux 100 G-force Washers N-Series, Normal Spin for Coin/Card

Electrolux washers feature Compass Pro, low water consumption, and robust design.

Electrolux Professional 100 G-Force extraction normal spin washers combine world-class reliability with innovative features and programmability.

Electrolux washers increase your productivity, lower utility costs, and provide significant electrical and gas savings. With innovative design and high performance features, Electrolux washers come standard with Compass Pro for easy customization and flexibility.

Features and Benefits:

- Low water and energy consumption
- Convenient four compartment detergent box
- Large, secure coin box
- Heavy-duty construction with robust steel door and lock, hinges set wide apart and door locked through entire wash cycle
- Stainless and galvanized steel in all vital parts for maximum rust protection
- SuperBalance guarantees the correct extraction force, longer machine life
- Single phase electrical for easy installation & lower costs

Compass Pro microprocessor offers:

- Large display and one control knob for easy program selection
- More than 20 languages available – displays two languages simultaneously
- Real-time clock for time-of-day pricing, happy hour pricing and promotions
- Revenue generating quick selection and option buttons for the most frequently used wash programs and options
- Detailed user statistics and programmability



Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



Designed by experts. Inspired by you.

For more information, please visit www.laundrylux.com

Wascomat "W" Series, 100G Washers	W575N		W5105N		W5130N		W5180N		W5250N		W5330N	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	28 3/4	730	27 3/4	705	31 1/8	825	34 5/8	880	37 5/8	955	40 15/16	1040
Height (in/mm)	43 7/8	1115	47 1/4	1200	47 1/4	1200	52 1/2	1333	55 1/2	1410	56 7/8	1445
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft ³ /l)	3.0	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	20 1/2	520	23 7/16	595	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Cylinder depth (in/mm)	16 5/16	414	17 11/16	450	18 7/16	468	21 5/16	542	23 7/8	606	26 3/16	665
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	32 1/2	825	35 13/16	910	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	40 9/16	1030	43 7/8	1115	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	375+/-696	1.7+/-3.1	468+/-813	1.9+/-2.5	518+/-912	2.4+/-3.1	611+/-1057	2.9+/-3.9	842+/-1189	3.8+/-4.9	1019+/-1310	4.6+/-5.6
Dynamic frequency (Hz)	9.3		9.1		9.1		8.8		8.3		7.9	
Noise level (dBA)	65		71		71		76		71		77	
Crated weight (lb/kg)	344	156	368	167	432	196	528	240	666	302	719	326
Operating Speeds												
Wash (rpm)	52		46		46		44		42		40	
Extract (rpm/G-Force)	587 / 100		548/100		548/100		525/100		497/100		474/100	
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~	
Full-load current (Amps) / Ckt breaker (Amps)	3.5 / 15		3.8 / 15		3.8 / 15		5.5/15		6.9 / 15		6/15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7/15		7.6 / 15		7.6 / 15		9.5 / 15		13.2 / 20		-	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.



Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Extended lifetime due to Super Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



Greatest flexibility with Compass Pro®

- Real-time clock for time of day & happy hour pricing
- Multi-language menu selection
- Text & voice guidance options
- Easy to program, easy to use

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

